

Offshore Series

Our Offshore double hull tender is sized from 520cm to 950cm. These hulls are made of 4mm or 5mm thick powder coated marine grade aluminum (depending on model), and 1100 Dtex PVC fabric or hypalon fabric for inflatable tube. This boat hull has a luxury design with rear seats, an integrated fuel tank and reinforced keel. With the impermeable qualities of our aluminum hull, there is no need to worry about gelcoat chips, or putting the boat on a beach or a trailer. This boat is easy to trailer, easy to launch and recover due to their light weight and integrated davit lifting eyes. They all can be towed on an unbraked trailer.



Standard features:

- High tensile chromated & powder coated aluminum hull (24° Deadrise)
- 1100 Dtex PVC fabric
- Integrated transom supports
- Integrated inside keel
- Lockable bow locker
- Flush mount non-return valves
- Self-draining valve
- Safety valves
- Lifting points and towing eyes
- Anti-slip EVA pad
- Full length keel guard
- Rear seat with sea cushions
- Outside and inside reinforced motor pad
- One pair of aluminum oars
- Foot pump
- Repair kit

Optional features:

- Hypalon fabric (Taiwan or Orca)
- Anchor holder
- Console and seat
- Roll bar with navigation lights
- Boat trailer
- Electric pump
- Dry bag
- Sunshade
- Boat cover
- Fishing rod holder

Specification:

Model	Overall length		Internal width (cm)	Overall width (cm)	Tube diameter (cm)	Chamber (room)	Max power (hp)	Capacity (person)	Max loading (kg)	Aluminum hull thickness (mm)
	(cm)	(feet)								
BB520	520	17.06	130	240	52	5	100	10	1000	4
BB600	600	19.68	140	260	56	6	150	12	1255	4
BB660	660	21.65	140	260	56	6	200	14	1405	4
BB700	700	22.96	175	290	56	6	200	14	1450	10+5+4
BB760	760	24.93	175	290	56	6	300	15	1480	10+5+4
BB860	860	28.21	175	290	56	6	500	20	2106	10+5+4
BB950	950	31.16	175	290	56	6	700	25	2600	10+5+4

All measurements in metric. 2.54 cms = 1 inch, 1 kg = 2.2 lbs.